


50 classic **box** - SVR050CLA-BOX1000-DA2830080-WHT



<b>IK17</b>	175 joules impact resistance
<b>IP66</b>	hermetically sealed light module cassette
<b>AT06</b>	security torx tamper-proof fasteners

**country of origin**  
Australia

<b>range</b>	50 classic box
<b>product code</b>	SVR050CLA-BOX1000-DA2830080-WHT

**accreditations**  
Australian Made and Owned  
DALI Alliance  
EESS  
RCM


<b>description</b>	Heavy-gauge extruded aluminium mounting base and end caps with durable polyester powder coat finish Impact-resistant, UV-stabilised and high-transmission polycarbonate light module cassette Serviceable, replaceable and upgradable light module cassette Internal socket drive security-torx 304 stainless steel security fasteners Integral energy efficient Zhaga compliant Tridonic LED modules and power supply unit Direct-fix surface mounted Internal stainless steel wire safety lanyards 1.0 m circular flex connection
--------------------	--

**warranty**  
7-year standard  
10-year on application

<b>applications</b>	extremely robust surface mounted luminaire that enhances safety and security in the most challenging environments. a durable construction ensures dependable operation and superior performance under harsh operating conditions; ideal for applications such as transportation, custodial, public areas, and secure healthcare
---------------------	---

**standards**  
AS/NZS 60598.1:2017  
AS/NZS 60598.2.1:2014  
AS 60529-2004  
IEC/EN 62262:2002+A1:2021  
ANSI/IES LM-79-19  
ANSI/IES LM-80-21  
ANSI/IES TM-21-21

**polar curve**



50 classic **box** - SVR050CLA-BOX1000-DA2830080-WHT



**driver**


manufacturer	Tridonic
control interface	DALI-2
dimming range	1 – 100 %
switch-on time	< 700 ms
switch-off time	< 50 ms
rated lifetime	> 100,000 h

**light source**

manufacturer	Tridonic
technology	linear LED module
operating mode	constant current
delivered lumens	2381 lm
colour rendering index	80
correlated colour temperature	3000 K
colour tolerance	3 SDCM
CTI	≥ 600 V
lumen maintenance [L80F10]	> 72,000 h

**electrical**

rated supply voltage	220 – 240 V
mains frequency	0 / 50 / 60 Hz
power consumption	29.97 W
leakage current	< 350 µA
in-rush current	22.4 A / 176 µs
power factor [	0.97
THD	8%
overvoltage protection	320 V AC / 48 h
mains surge protection [L-N]	1 kV
mains surge protection [L/N-PE]	2 kV



**dimensions [mm]**

L - length	970
W - width	75
H - height	105

**mounting**

type	surface
method	direct-fix or wall bracket
orientation	horizontal or vertical burning position

**mounting base + end caps**

material	extruded aluminium base + security end caps
finish	white texture polyester powder coat

**light module cassette**

material	high-transmission + uv-stabilised extruded polycarbonate [hermetically sealed]
finish	clear reeded

**maximum circuit breaker loads**

conductor size	1.5mm <sup>2</sup>		2.5mm <sup>2</sup>		1.5mm <sup>2</sup>		2.5mm <sup>2</sup>	
circuit breaker type	C10	C13	C16	C20	B10	B13	B16	B20
luminaire quantity	21	28	36	45	13	17	22	27