

50 classic **box** - SVR050CLA-BOX1500-DA2865100-BLK



- IK17** 175 joules impact resistance
- IP66** hermetically sealed light module cassette
- AT06** security torx tamper-proof fasteners

**country of origin**  
Australia

- range** 50 classic box
- product code** SVR050CLA-BOX1500-DA2865100-BLK

- accreditations**
- Australian Made and Owned
  - DALI Alliance
  - EESS
  - RCM

**description**

Heavy-gauge extruded aluminium mounting base and end caps with durable polyester powder coat finish

Impact-resistant, UV-stabilised and high-transmission polycarbonate light module cassette

Serviceable, replaceable and upgradable light module cassette

Internal socket drive security-torx 304 stainless steel security fasteners

Integral energy efficient Zhaga compliant Tridonic LED modules and power supply unit

Direct-fix surface mounted

Internal stainless steel wire safety lanyards

1.0 m circular flex connection

**warranty**

- 7-year standard
- 10-year on application

**applications**

extremely robust surface mounted luminaire that enhances safety and security in the most challenging environments. a durable construction ensures dependable operation and superior performance under harsh operating conditions; ideal for applications such as transportation, custodial, public areas, and secure healthcare

- standards**
- AS/NZS 60598.1:2017
  - AS/NZS 60598.2.1:2014
  - AS 60529-2004
  - IEC/EN 62262:2002+A1:2021
  - ANSI/IES LM-79-19
  - ANSI/IES LM-80-21
  - ANSI/IES TM-21-21

**polar curve**



50 classic **box** - SVR050CLA-BOX1500-DA2865100-BLK



**driver**

manufacturer	Tridonic
control interface	DALI-2
dimming range	1 – 100 %
switch-on time	< 600 ms
switch-off time	< 20 ms
rated lifetime	> 100,000 h



**light source**

manufacturer	Tridonic
technology	linear LED module
operating mode	constant current
delivered lumens	5150 lm
colour rendering index	80
correlated colour temperature	6500 K
colour tolerance	3 SDCM
CTI	≥ 600 V
lumen maintenance [L80F10]	> 72,000 h

**dimensions [mm]**

L - length	1530
W - width	75
H - height	105

**electrical**

rated supply voltage	220 – 240 V
mains frequency	0 / 50 / 60 Hz
power consumption	62.44 W
leakage current	< 230 µA
in-rush current	23.0 A / 174 µs
power factor [	0.98
THD	6%
overvoltage protection	320 V AC / 48 h
mains surge protection [L-N]	1 kV
mains surge protection [L/N-PE]	2 kV

**mounting**

type	surface
method	direct-fix or wall bracket
orientation	horizontal or vertical burning position

**mounting base + end caps**

material	extruded aluminium base + security end caps
finish	black texture polyester powder coat

**light module cassette**

material	high-transmission + uv-stabilised extruded polycarbonate [hermetically sealed]
finish	clear reeded

**maximum circuit breaker loads**

conductor size	1.5mm <sup>2</sup>		2.5mm <sup>2</sup>		1.5mm <sup>2</sup>		2.5mm <sup>2</sup>	
circuit breaker type	C10	C13	C16	C20	B10	B13	B16	B20
luminaire quantity	21	28	35	45	13	17	21	27