

50 classic **suspended** - SVR050CLA-SUS1500-DA2930040-BLK



IK17	175 joules impact resistance
IP66	hermetically sealed light module cassette
AT06	security torx tamper-proof fasteners

country of origin
Australia

range	50 classic suspended
product code	SVR050CLA-SUS1500-DA2930040-BLK

accreditations
Australian Made and Owned
DALI Alliance
EESS
RCM


description	Heavy-gauge extruded aluminium mounting base with durable polyester powder coat finish and impact-resistant GRP security caps Impact-resistant UV-stabilised high-transmission polycarbonate light module diffuser Serviceable replaceable and upgradable light module cassette Internal socket drive security-torx 304 stainless steel security fasteners Integral energy efficient Zhaga compliant Tridonic LED modules and power supply unit Heavy-gauge stainless steel wire suspensions Internal stainless steel wire safety lanyards 1.0 m circular flex connection
--------------------	--

warranty
7-year standard
10-year on application

applications	extremely robust suspended mount luminaire that enhances safety and security in the most challenging environments. a durable construction ensures dependable operation and superior performance under harsh operating conditions; ideal for applications such as transportation, custodial, public areas, and secure healthcare
---------------------	---

standards
AS/NZS 60598.1:2017
AS/NZS 60598.2.1:2014
AS 60529-2004
IEC/EN 62262:2002+A1:2021
ANSI/IES LM-79-19
ANSI/IES LM-80-21
ANSI/IES TM-21-21

polar curve



50 classic **suspended** - SVR050CLA-SUS1500-DA2930040-BLK



driver

manufacturer	Tridonic
control interface	DALI-2
dimming range	1 – 100 %
switch-on time	< 600 ms
switch-off time	< 20 ms
rated lifetime	> 100,000 h

light source

manufacturer	Tridonic
technology	linear LED module
operating mode	constant current
delivered lumens	2271 lm
colour rendering index	90
correlated colour temperature	3000 K
colour tolerance	3 SDCM
CTI	≥ 600 V
lumen maintenance [L80F10]	> 72,000 h

electrical

rated supply voltage	220 – 240 V
mains frequency	0 / 50 / 60 Hz
power consumption	24.98 W
leakage current	< 230 µA
in-rush current	23.0 A / 174 µs
power factor [0.98
THD	6%
overvoltage protection	320 V AC / 48 h
mains surge protection [L-N]	1 kV
mains surge protection [L/N-PE]	2 kV



dimensions [mm]

L - length	1530
W - width	72
H - height	99

mounting

type	suspended
method	2.0 m heavy duty stainless steel
orientation	horizontal burning position

mounting base + end caps

material	extruded aluminium base + GRP security end caps
finish	black texture polyester powder coat + black GRP

light module cassette

material	high-transmission + uv-stabilised extruded polycarbonate [hermetically sealed]
finish	clear reeded

maximum circuit breaker loads

conductor size	1.5mm ²		2.5mm ²		1.5mm ²		2.5mm ²	
circuit breaker type	C10	C13	C16	C20	B10	B13	B16	B20
luminaire quantity	21	28	35	45	13	17	21	27